

MODEL: HS1-A

A hot stamping machine for application of holograms and signature panel



Partnerships in card solutions

Range of application

The machine is designed for application of holograms and signature panel on single card production. The machine is equipped as standard with a control unit that offers precise registration of single image holograms and ensuring low scrap rates.

Advantages

- Single magazine in the card input station and the card collection station.
- Hot stamping station.
- Micro adjusting of hot stamping depth.
- Changeable stamping head for various foil widths.
- Adjustable hot stamping temperature depending on the foil size and card type.
- The hot stamping head is able to stamp on different position of the card by adjusting the X axes and Y axis. The materials unwind and rewind are able to control foil material tension by brake devices for precise positioning.

Specifications

MODEL	HS-1A
Card width	53.92~54.03 mm
Card Length	85.47~85.72 mm
Card thickness	0.8 mm (±0.4 mm)
Maximum stamping size	48×85 mm
Stamping tolerance	± 0.15 mm
Card output	Max. 6000 card/hr
Electronic temperature control	50~400□
Power	220v, 1 phase , 1kw
Air connection	6-8 bars
Dimensions	1300(L) ×1100(W) × 1500(H) mm
Net weight	650 kg



VICCARD PTE LTD
1020 Tai Seng Avenue #03-3500,
Singapore 534416
Tel: (65) 6288 1801
Fax: (65) 6288 1802
Email: viccard@singnet.com.sg

VICCARD (M) SDN BHD
Unit A-3-11, 8 Avenue, Jalan 8/1, Seksyen 8
46050 Petaling Jaya, Selangor, Malaysia
Tel: (603) 7960 7932 / 7954 7932
Fax: (603) 7960 0932
Email: viccard@po.jaring.my

www.viccard.com.sg