



Card Solutions For A Better World

CIM PRO-SERIES Model E-1000 EMBOSSE

FEATURES

STANDARD



OPTIONAL



USED BY:

- BANKS/CREDIT INSTITUTIONS
- INSURANCE COMPANIES
- CASINOS
- CLUBS/ASSOCIATIONS
- GOVERNMENT OFFICES
- SERVICE BUREAUS

IDEAL FOR:

- CREDIT CARDS AND OTHER FINANCIAL CARDS*
- RFID CARDS
- GIFT CARDS
- RFID CARDS
- PREPAID CARDS

** Compatible with most 3rd party EMV personalization software solutions*

IN LINE SOLUTIONS:

- MF 6000
- T 1000/2000
- CAM 3030
- CAM 8080

SOFTWARE



The E1000 Pro-Series card embossing machine (Desktop/Stand version) is able to obtain a highly customizable plastic card personalization: it can manage embossing, infill and tipping, magnetic stripe and / or contact and contactless smart card encoding into one single card flow.



CARD EMBOSSEING SOLUTION DESKTOP DIMENSIONS WITH HEAVY DUTY PERFORMANCE


- ✓ 105 characters capacity drum - 120 available on request
- ✓ Dual Infill for front and rear in one pass
- ✓ Magnetic Stripe encoding (JIS/ISO)
- ✓ Regular VISA + VISA Mini Card encoding
- ✓ Smart Card Contact and Contactless unit



Card Solutions For A Better World

CIM PRO-SERIES Model E-1000 EMBOSSE

TECHNICAL FEATURES



Infill unit

1000
EMBOSSER

MULTICARD
2013

POWERCARD
INTEGRATION



Card Solutions For A Better World

CARD & FEEDER

dimensions	CR80 - ISO standard
thickness	0.76 ± 0.08 mm / 30 ± 3.15 mil
materials	ABS, PVC and composite. Semi transparent PET-G available on request
input hopper	200 cards capacity
output hopper	200 cards capacity with FIFO (first in – first out) technology; reject hopper 10 cards capacity

EMBOSSING

technology	Embossing or Indent
drum capacity	105 characters
characters	Standard Gothic, OCR7B, country specific characters (optional), Braille drum/types (optional), etc.
embossing area	9 lines x 31 characters (76 x 45 mm area / 3 x 1.77 in)
internal tipper unit	off-line tipping option (76 x 41 mm area / 3 x 1.61 in). Ribbon saving function
infill unit	options: single or dual infill Dual infill is a device for front (i.e. OCRB1/B4 fonts) and rear (i.e. CVV2 - OCRA1) infill embossing in one pass
performance	Up to 500 CPH depending on the job

ENCODING OPTIONS

magnetic encoding	optional: 3 ISO 7811 tracks, LoCo, HiCo, JIS optional: regular VISA + VISA Mini Card (paired)
smart card unit	optional: contact and contactless

INTERFACE & SOFTWARE

communication interf.	RS232 serial port
operating system	Multicard compatible with Windows XP/Vista/7.
application program	User interface monitoring, card production control, automatic card remake option, pre-encoded card and smart card reading with complete processing operation, database connection, system status and help messages displayed on PC.
software application (optional)	PowerCard Integration : The PowerCard Integration software is capable of managing the whole production process, from data import to card mailing, supervising multiple production lines simultaneously and ensuring complete integrity of the production area in real time. PowerCard Integration is the perfect application for production environments where a high throughput and a wide range of jobs are the norm.
SDK option	available on request

HARDWARE

power supply	100 - 117 - 220 - 230 or 240 Volts - 50/60 Hz
operating environment	5 ÷ 40 °C / 41 ÷ 104 °F
dimensions (WxDxH)	860 x 480 x 350 mm / 33.9" x 18.9" x 13.8"
weight	62 kg / 137 lbs
floor stand	optional (required for in-line operation)

SINGAPORE

VICCARD PTE LTD
Tel: +65 6265-2998
Email: viccard@singnet.com.sg
www.viccard.com.sg

MALAYSIA

VICCARD MALAYSIA SDN BHD
Tel: +603 7960-7932
Email: sales@viccard.com.my
www.viccard.com.my